

Rubiomonocoat PRECOLOR EASY

CREATIVE ZONE

DESCRIPTION:

Rubio Monocoat Precolor Easy is a pre-colour, designed to be used in combination with the **RMC Oil Plus 2C**, to create unique colour effects.

The option to choose a combination of 14 different pre-colours with a finish in one of the 40 colours of the **RMC Oil Plus 2C** range allows unlimited creative possibilities, while the optimal molecular bonding of the **RMC Oil Plus 2C** with the wood remains guaranteed (moreover the **RMC Precolor Easy** colors can be inter-combined).

SPECIFIC FEATURES:

- Natural look
- Can also be applied with a polisher
- 14 unique colours
- Unlimited combinations possible

APPLICATION:

1. Sand the surface according to professional standards.
When renovating old floors, you must remove all the residues from previous treatments completely (varnish, oil, wax, etc.).
2. Vacuum the surface and clean with **RMC Cleaner**.
3. Stir the product well using a stirring rod.

Manual application:

- Cover the wood completely with **RMC Precolor Easy**, using a brush or the special **RMC Brush Standard 220** on steel.
- Spread evenly using a lint-free cloth.
- Work in areas sized to allow manual touch-ups without having to tread the finished area.

Mechanical application:

- Cover the wood completely with **RMC Precolor Easy**, preferably using the special **RMC Brush Standard 220** on steel.
 - Spread the product using a floor polisher with a white pad until no circles are visible.
 - Then wipe the borders with a non-fluffy cloth until even.
 - Work in areas sized to allow manual touch-ups without having to tread the finished area.
4. Allow the surface to dry for 1 to 3 hours. The exact drying time depends on the foundation, moistening, temperature and ventilation.
When dry, any overlapping can be removed by locally applying **RMC Precolor Easy** until even.
 5. Apply the **RMC Oil Plus 2C**.
Please consult the technical data sheet of the oil for the correct application of this product!

If any wood fibres are still upright, you will need to grind these using a floor polisher equipped with a beige pad.
Afterwards, vacuum thoroughly.

Remark:

Do not use in combination with water based finishing products!

CONSUMPTION:

Depending on the sort of wood and the preparation, about 80 to 100 g/m².

These usages are merely indicative. It is always recommended to make a sample in order to calculate the exact usage.

TECHNICAL CHARACTERISTICS:

Physical state at 20 °C: liquid

Flash point [°C]: N/A

Density: between 1 kg/L and 1,16 kg/L according to colour

VOC content: 0 g/L

Solubility in water: 100 %

STORAGE:

The product can be stored for up to 12 months.

Store in dry conditions, in the original packaging, at a temperature of 5 to 25°C.

The product is frost sensitive, use frost-free storage and transport only.

PACKAGING:

Bottle 100 ml, can 1 L, 2,5 L and 5 L

PROVIDED BY:

DISCLAIMER: It is the responsibility of the user to determine through own testing whether the product is suited for its chosen application. Muylle Facon NV is not liable for any resultant damage. The above information may be subject to amendments, which will be published in revised versions of the technical sheet. We waive all responsibility for unsatisfactory results that are due to causes unrelated to the quality of the product. This technical information has been collected on the basis of current information and knowledge. The most recent technical sheets can be requested or are available on the website.



Consult the safety sheet before use.
Date TDS: 15/04/13

MUYLLE FACON



MADE IN BELGIUM by N.V. MUYLLE - FACON S.A.
Ambachtenstraat 58 - B-8870 Izegem (Industriezone Abele)
Tel. +32 (0)51 30 80 54 - Fax + 32 (0)51 30 99 78 - HRK 1823
info@muyllefacon.be - www.rubiomonocoat.com

