

Rubio Invisible Protector

Plant-based protection that preserves the natural look of wood

Rubio® Invisible Protector is a protection that preserves the natural look of wood, based on a high-quality plant-based emulsion. The original surface gets a durable protection with an invisible finish. You can apply Rubio® Invisible Protector on almost all wood types and it also preserves the natural look and feel of darker wood types. Rubio® Invisible Protector is based on a revolutionary plant-based resin.



PRODUCT INFORMATION

› Unique characteristics

- 100 % invisible look
- Based on a plant-based resin and water
- 1 component
- Low consumption: 12-14,5 m²/L per layer
- Excellent wear and UV resistance (non-yellowing)
- Superior resistance to burnishing/polishing (mar resistance)
- Suitable for almost all indoor wooden surfaces including dark wood species
- Easy to apply on brushed and sanded wood
- Natural look and feel of wood are preserved
- Transparent finish
- Limited chance for overlaps or roller marks
- Can be used on top of Rubio Monocoat Pre-Aging without changing the colour
- VOC 2010 compliant

REMARK

Cleaning and maintenance: please consult the technical data sheet of Rubio Surface Cleaner for detailed instructions.

› Technical characteristics

- 1 component plant-based resin
- Solid content 25-30 %
- VOC content < 2 %
- NMP-free
- APEO-free
- Liquid at 20 °C
- Milky white liquid
- Non-flammable
- Specific density ca. 1 at 20 °C
- Mild odour

› Storage

The product can be stored up to 12 months in dry conditions and in its original packaging. Keep away from frost.

› Packaging

- 1 L and 5 L jerrycan
- 20 L can

› Consumption

12-14,5 m²/L per layer

These usages are merely indicative. Results depend on wood type and method of preparation. It is always recommended to make a sample in order to calculate the exact usage.

APPLICATION INFORMATION

› Application by roller on untreated wood

- STEP 1** Sand the surface according to the desired smoothness (grit 120) and make sure the surface is free of scratches. Thoroughly remove sanding dust with a vacuum cleaner. Finish the floor immediately after sanding (because of the oxidation of the wood).
- STEP 2** Let Rubio Invisible Protector stabilize to room temperature (ideally between 18 and 25 °C). Ideal humidity is not over 70 %. Shake the Rubio Invisible Protector jerrycan thoroughly until any settlement has disappeared.
- STEP 3** Apply the first layer of Rubio Invisible Protector (see point 2: Tips & tricks) using Rubio White Roller with a consumption of ca. 80 g/m². Allow to dry for 3-4 h.
- STEP 4** Apply the second undiluted layer onto the surface with Rubio White Roller with a consumption of ca. 75 g/m². Leave to dry 16 to 24 h (overnight).
- STEP 5** We recommend intermediate sanding with a 220/240 grit and removing the sanding dust thoroughly before applying the final coat. Apply the final coat with a consumption of ca. 75 g/m² (see step 4). Leave to dry 16 to 24 h (overnight).

› Tips & Tricks

- To achieve the best results, Rubio Invisible Protector must be applied immediately after sanding.
- Add 10 % water for the first layer on highly absorbent substrates or at higher temperatures.
- When the product is poured out, we recommend waiting for 5 minutes to start working. This allows the air bubbles to disappear before applying the product.
- Make sure to work with a well saturated roller (an unsaturated roller gives an uneven result).
- We recommend using a new roller after each layer.
- Always try to work wet in wet to avoid overlaps or drying marks.
- It is better to work in lanes of 0,5-meter-wide and covering the total width of the room to finish.
- Make sure the underfloor heating is deactivated, preferably a couple of days before the job.
- Try to avoid too much ventilation during the application, this to prevent drying too fast.
- We recommend keeping doors and windows closed.
- Avoid direct sunlight on the surface.
- Rubio Invisible Protector is not compatible with Rubio Monocoat Tannin Primer, Rubio Monocoat WoodPrep, Rubio Monocoat Smoke, Rubio Monocoat Fumed and Rubio Monocoat Precolor Easy


› Tools



REMARK

The used tools must be cleaned with water after application.

› Related products



Check the packaging and the safety data sheet for more details.

For our complete assortment of products for the protection and colouring of interior and exterior wood, please visit www.rubiomonocoat.com

YOUR DISTRIBUTOR:

LIABILITY: It is the user's responsibility to establish, through his own tests, whether the product is suitable for the chosen application. In no case can Muylle Facon BV be held liable for any consequential damage. The information above may be subject to changes, which will be published in the updated versions of the technical data sheet. We cannot be held liable for poor results due to causes that are not related to the quality of the product. This technical information has been drawn up based on the currently available information and knowledge. The most recent technical data sheets can be requested or are available on the website.
Date of TDS: 13/08/2020. Check the safety information before using the product.



Rubio® MONOCOAT

MUYLLE  FACON

Muylle Facon BV
 Ambachtenstraat 58
 8870 Izegem (BELGIUM)

Phone +32 (0) 51 30 80 54
 Fax +32 (0) 51 30 99 78
 info@muyllefacon.be

www.rubiomonocoat.com